

Specifications

General

Tape Format: 1/2" VHS
 Rewind Time: ~65 sec. (T-120)

Video Recording Time

RT: 6, 18, 30
 TL: 72, 96, 120, 168, 240, 480, 960 hr

Audio Recording Time

Linear Audio Rec.: 6, 18, 30 hr

Back Up Time

30 days

Timer

24-hour

Video Signal

NTSC/EIA (525 lines, 60 fps)
 1.0Vp-p (75 Ohms)

Resolution

300 TVL (B/W), 250 TVL (color)

Connections

Video In/Out: BNC
 Audio In/Out: RCA
 I/O Terminals: push-type terminal strip (12)

Dimensions (W x H x D)

14.2" x 3.7" x 10.7"

Weight

8.4 lbs (3.8 kg)

Power

15 Watts maximum

Operating Temperature

32°F ~ 95°F (0°C ~ 35°C)

Operating Humidity

Less than 80% RH

Optional Accessories	
XDLBW2	VCR lock box
A-A2VCBNC	VCR-to-monitor cable, 6', BNC/RCA connectors
A-AB50C	50' BNC to BNC cable

Record/Playback Modes					
Rec/Play Mode	T-120	T-160	Recorded Fields/Sec.	Tape Drive	Audio Recording
6H	6-hour	8-hour	60	High Density	Yes
18H	18-hour	24-hour	20	High Density	Yes
30H	30-hour	40-hour	12	High Density	Yes
72H	76-hour	101-hour	1.67	Time Lapse	No
96H	96-hour	127-hour	3.53	Time Lapse	No
120H	120-hour	160-hour	1.0	Time Lapse	No
168H	172-hour	229-hour	0.71	Time Lapse	No
240H	240-hour	319-hour	1.46	Time Lapse	No
480H	484-hour	645-hour	0.25	Time Lapse	No
960H	964-hour	1285-hour	0.125	Time Lapse	No

